

AC Input Characteristics	AC Input Voltage	400VAC
AC Output Characteristics	Input Type	3P + N + PE
	AC Input Current	16A/phase
	Frequency	50/60Hz
	AC Output Voltage	400VAC
Operating Conditions	Power	11 kW (upgradable to 22kW)
	AC Output Current	16A/phase
	Operating Temperature	-25 °C – 50°C
	Storage Temperature	-30°C – 70°C
	Humidity	5% – 95% RH (without condensation)
	Installation Altitude	Up to 2000m
Construction	Enclosure	Galvanized Steel, Polycarbonate (capability for anti-graffiti coating)
	IP rating	IP55
	Mechanical Impact IK	IK10
	Display	LCD 4,3"
	Outputs	Type 2 socket-outlet or Mode 3 tethered cable with Type 2 outlet (5m)
	Dimensions	300x575x165mm (width x height x depth)
	Dimensions on base	Ground:440x1534x165mm, Wall:300x575x165mm
	Weight	Wall base: With tethered cable 18,9kg , With socket outlet 17,2kg Ground Base: With tethered cable 60,6kg , With socket outlet 58,9kg
	Energy Meter	MID Certified 3-Phase energy meter
Electronic Parts	Protective Devices	Overvoltage (OVP) & Undervoltage (UVP) Protection
		Ground Loss Detection
		Overtemperature Protection (OTP)
		RCD (Residual Current Protection) with AC leakage detection 30mA and DC smooth current detection 6mA and circuit breaker MCCB Type C*
		Surge Protection SPD Type 2*
	Communication Protocol	S2W & OCPP 1.6 JSON
	Language Menu	Greek, English **
	User Identification	RFID
	Connectivity	Ethernet or WiFi or GSM
Charging	Time	3-4 hours
Installation		
	Level Of Grid Power Supply	No 1 – Maximum Agreed Power 15kVA 3-phase from Network Operator ***
	ATEX zones	Installation outside ATEX zones
	Grid Substation	Not Applicable
	Cable Cross Section	5x6mm2(cable length up to 100m), 5x10mm2 (cable length up to 180m), 5x16mm2 (cable length up >180m)
Certifications	Regulations	IEC EN 61851-1:2019, IEC EN 61851-1:2017, IEC 61851-21-2:2018, EN 62196-1:2014, EN 62196-2:2016, CE
	Accredited Notification Body	DEKRA
Warranty		2 years